

MA

- ❖ 100% Gear driven transmission
- ❖ Premium appearance
- ❖ Three speeds
- ❖ Heat treated hardened steel alloy gears
- ❖ Full copper motor



Model	Transmission	Bowl Capacity(L)	Maximum Kneading Capacity(kg)	Maximum Flour(kg)	Motor Power(kw)	Voltage(V)	Agitator Speeds(RPM)	Dimensions(mm) A B C	Net Weight(kg)
MA10A	Gear	10	3.75	2.5	0.6	220	148/244/480	460*440*720	56
MA20A	Gear	20	7.5	5	1.1	220/380	130/234/418	500*460*900	86
MA25A	Gear	25	9	6	1.5	220/380	130/234/418	580*460*930	88
MA30A	Gear	30	10.5	7	2.3	220/380	165/270/560	630*530*1180	140
MA40A	Gear	40	13.5	9	2.38	220/380	165/270/560	660*560*1210	150

BM

- ❖ Gear and belt transmission
- ❖ Low noise operation
- ❖ High-end design
- ❖ Three speeds
- ❖ Heat treated hardened steel alloy gears
- ❖ Full copper motor



Model	Transmission	Bowl Capacity(L)	Maximum Kneading Capacity(kg)	Maximum Flour(kg)	Motor Power(kw)	Voltage(V)	Agitator Speeds(RPM)	Dimensions(mm) A B C	Net Weight(kg)
BM10N	Gear+belt	10	3.75	2.5	0.6	220	118/234/460	480*420*820	58
BM20N	Gear+belt	20	7.5	5	0.9	220/380	140/276/540	570*480*950	78
BM30N	Gear+belt	30	10.5	7	1.3	220/380	134/234/460	690*650*1250	135
BM40N	Gear+belt	40	13.5	9	1.3	220/380	134/234/460	690*650*1250	138

B7 / B10B

- ❖ 100% Gear driven transmission
- ❖ Five speed & digital timer
- ❖ Aluminum alloy body
- ❖ #5 Attachment Hub (Option)



B7A



B7B



B7C



B10B

Model	Transmission	Bowl Capacity(L)	Maximum Kneading Capacity(kg)	Maximum Flour(kg)	Motor Power(kw)	Voltage(V)	Agitator speeds(RPM)	Dimensions(mm) A B C	Net Weight(kg)
B7A	Gear	7	1.2	0.8	0.65	220	230-580	440*350*510	20
B7B	Gear	7	2.25	1.5	0.65	220	126/252/545	440*350*510	24
B7C	Gear	7	1.2	0.8	0.65	220	230-580	440*350*510	25
B10B	Gear	10	3	2	0.65	220	126/252/545	540*420*700	30