

* Metal Case/ EMC




TABLE DROP-IN						
DESCRIPTION						
MODEL		BKT18-E				
Operating Voltage		220V, 60Hz, 1PH				
Power Consumption		1800 W				
Amperage		8 A				
Heating Power Setting		Warming : 2 Steps				
		Cooking : 6 Steps				
Dimension (mm)		297 X 370 X 80 (mm)				
Weight		5 KG				
Control Method		Touch				
Product Type		Built-In				
Cookware Diameter		MIN : Ø 130 mm				mm
Loadable Weight (kg)		MAX 30 Kg				
Time Required	Capacity	5L (10 portions)		portions)	15L (30	portions)
	Time	Approx. 13 min 30 sec		27 min	Approx 40	min 20 sec
for Boiling Water	Note	 ※ one portion converted into 500ml ※ start point: 25 ♥ (room temperature) ※ the abovementioned time can be changed according to actual environment/each different situaton 				
Main Function		■ Safety				
		Over-current indication: Error E1 Over-voltage indication: Error E2 (above 260V) Low-voltage indication: Error E3 (below 180V)				
		- Product super-heating indication: Error E4				
		(internal temperature above 80°C)				
		- Top overheating indication: Error E6 (above 230°C) ■ Warming : H1~ H2 (35°C ~ 60°C)				
		■ Cooking: 3 ~ 8				
Comparis	Item	Induction (1 h	ole)	City Gas (1 hole)		
	kw	1.8		4.64		
on	kcal/h	1551.72		4000		
	kcal/h	1396.548 (90% of efficiency) 2000 (50% of efficiency)				
After-Sales Service		1-year warranty (to be charged in case of consumer's negligence)				

IMPLEMENTATION

Applications






Product Use


- For Shabu-Shabu, stew, blowfish soup etc which requires strong heating power
- Can be extended to 2-hob or multi-hob range
- Great side-bar cooking for Island table
- Group meal for a small number of people

* Remarks



* Please be advised that it's necessary to keep 10cm of distance from the front/rear side of the unit

2. Hole-punching size for stainless guide (*guide sold separately) 377



www.dipoelec.com