

dipo

dipo
INDUCTION

For The Green Cook

Sys Cook

Heavy equipment for commercial main kitchen
Highest energy efficiency about 90%
Absolutely safe and economic
Very high power for cooking



	Counter-top Range		Induction Low Range		Induction Griddle	
Product Picture						
Model	TCK070-E	TCK113-E	DIH070-E	DIH113-E	DIHG450-E	DIHG900-E
Max Output	7500W	10500W	7500W	10500W	3300W	6600W
Amperage	11.5A	16A	11.5A	16A	15A	30A
Electric requirements	380V(340~420V) / 3PH+N 50 / 60Hz				220V(208~240V) / 1PH 50 / 60Hz	
Dimension(mm)	450X600X280		600X750X370		450X600X280	900X600X280
Weight(kg)	24kg		44kg		42kg	78kg
Heating mode	8 steps		10 steps		8 steps	10 steps
Warming mode	7 steps				N/A	
Timer mode	1 sec ~ 720 min				N/A	
Temperature mode	60 ~ 200°C				40 ~ 200°C, per 5°C	
Warranty	1 year					

Features

Heavy duty line for commercial kitchen	Reaches 150°C by 5 min 30 sec
Support various functions for expert chef (timer mode, temp. mode)	Precise temperature controls, within ±2°C range
Cooking mass capacity of food up to 100L	Very even surface temperature
Reduce kitchen temperature more than 10°C	Separated 2 temperature zone (DIHG900-E)

