



RIIII T-IN (SINGLE HOLE)



* Metal Case/ EMC



BUILT-IN (SINGLE HOLE)				
DESCRIPTION				
Part No.		NBK35-E		
Operating Voltage		208/240V , 50/60Hz 1PH		
Power Consumption		Max Output: 3300W		
Amperage		Total: 15A		
Heating Power Setting		Warming: 7 Steps (H1~H7)		
		Cooking: 10 Steps		
Dimension (mm)		Product: 297*370*80	, Packing: 350*505*165	
Weight (kg)		6		
Control Method		Separate panel with encoder/ button		
Product Type		Built-in		
Cookware Diameter		Min: Ø 125 mm , Max: Ø 240mm		
Loadable Weight (kg)		Max. 60		
Time Required for Boiling Water	Capacity		15L (30 portions) 20L (40 portions)	
	Burner	Approx. 10 min. Approx. 20 min	Approx. 33 min. Approx. 45 min.	
	Note	 ※ one portion converted into 500ml ※ start point: 25 ℃ (room temperature) ※ the abovementioned time can be changed according to actual environment/each different situaton 		
Main Function		■ Safety - Over-current indication: Error E1 - Over-voltage indication: Error E2 (above 260V) - Low-voltage indication: Error E3 (below 180V) - Product super-heating indication: Error E4 (internal temperature above 80°C) - Top overheating indication: Error E6 (above 230°C) ■ Timer - Adjusting in second (range from 1sec through 720min) - One-time setting maintains until being initialized by power button ■ Warming: H1 ~ H7 (35°C ~ 90°C) ■ Cooking: 1 ~ 10 (same applies to both of 2 holes)		
	Item	Induction (1 hole)	City Gas (1 hole)	
Comparison	kw	3.5	4.64	
	kcal/h	3017.24	4000	
	kcal/h	2715.516 (90% of efficiency)	2000 (50% efficiency)	
After-Sales Service		1-year warranty (to be charged in case of consumer's negligence)		

IMPLEMENTATION

Application Examples

Product Use

■ For Shabu-Shabu, stew, blowfish soup etc which requires strong heating power




■ Can be extended to 2-hob or multi-hob range ■ Great side-bar cooking for Island table


■ Group meal for a small number of people

* Remarks


1. Control Built-in



3. Hole-punching size for stainless guide (*guide sold separately)



2. Table Built-in (in case of self-bending)



* Please be advised that it's necessary to keep 10cm of distance from the front/rear side of the unit