


MAIN KITCHEN INDUCTION



		DESCRIPTION					
Part No.		TCK35-E					
Operating Voltage		208/240V , 50/60Hz		1PH			
Power Consumption		Max Output:		3300W			
Amperage		Total:		15A			
Heating Power Setting		Warming: 7 Steps (H1~H7)					
		Cooking: 10 Steps					
Dimension (mm)		Product: 365*455*115 , Packing:		425*515*200			
Weight		7					
Control Method		Integrated panel with encoder/ button					
Product Type		Counter-top					
Cookware Diameter		Min: \varnothing 130 mm , Max: \varnothing 300 mm					
Loadable Weight (kg)		Max. 30					
Time Required for Boiling Water	Capacity	5L (10 Portions)	10L (20 Portions)	15L (30 Portions)	20L (40 Portions)		
	Time	A. Approx. 10 min	Approx. 20 min	Approx. 33 min	Approx. 45 min		
	Note	※ one portion converted into 500ml ※ start point: 25 °C (room temperature) ※ the abovementioned time can be changed according to actual environment/each different situation					
Main Function		■ Safety					
		- Over-current indication: Error E1					
		- Over-voltage indication: Error E2 (above 260V)					
		- Low-voltage indication: Error E3 (below 180V)					
		- Product super-heating indication: Error E4 (internal temperature above 80°C)					
		- Top overheating indication: Error E6 (above 230°C)					
		■ Timer					
		- Adjusting in second (range from 1sec through 720min)					
		- One-time setting maintains until being initialized by power button					
		■ Temperature Mode					
		- Dedicated temperature sensor needed (range from 60°C to 200°C, per 5°C)					
		- Precise temperature adjustment with less than $\pm 2\%$ of deviation (great advantage for fry cooking)					
		■ Warming: H1 ~ H7 (35°C ~ 90°C)					
		■ Cooking: 1 ~ 10 (same applies to both of 2 holes)					
		Item		Induction (1 hole)		City Gas (1 hole)	
		kw		3.5		4.64	
		kcal/h		3017.24		4000	
		kcal/h		2715.516 (90% of efficiency)		2000 (50% of efficiency)	
After-Sales Service		1-year warranty (to be charged in case of consumer's negligence)					