MKF 1011 C TS





Electric COMPACT combi oven







Innovation in the MILLENNIAL line is never an end in itself. The new design simplifies the use of the oven in everyday life. The constructive quality makes it last in time.

The renewed convection cooking system helps cook all 10 trays evenly. Innovation has only one purpose in the MILLENNIAL line: allows you to fully express yourself.

Plus

Patented fan guard system Airflowlogic™		
Patented system for direct steam Humilogic™		
Patented system for cooking chamber drying Drylogic™		
Available on request at the order	Voltage (V) : AC 220/230 3	
	Left side opening door	
Humidity management software		
Wi-Fi communication system		
Knob for quick selection of the touch screen		
Programmable oven start		

N ° 40 recipes stored

Control panel in 42 languages:

with touch screen


10 trays 1/1 GN

Arabic, Armenian, Azerbaijani, Bahasa (Indonesia), Bahasa (Malaysia), Bosnian, Bulgarian, Chinese, Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, Georgian, German, Greek, Hungarian, Icelandic, Italian, Japanese, Kazakh, Latvian, Lithuanian, Norwegian, Persian (Iran), Philippine, Polish, Portuguese, Romanian, Russian, Serbian, Slovenian, South Korean, Spanish, Swedish, Thai, Turkish, Ukrainian, Vietnamese

HACCP system

Adjustable door hinges 930 mm 501 mm 868 mm 418 mm 218 mm 422 mm 28 mm 28 mm Ó 972 mm E 921 05 mm 82 mm 56 mm 40 mm F 832 mm E 36





Equipment

Cardboard box dimensions with pallet (WxDxH mm)	570 x 980 x 1140 mm
Lateral supports	1 right + 1 left
Cable	Three-phase+neutra [5G 6]-L=1600 mm
USB port	
Multipoint core probe cod. MKSCMU	
Automatic washing system integrated	
Condensate collection how! with drain on do	or

Condensate collection bowl, with drain on door Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°

Optionals

optionals		
1/1 GN stainless steel 304 grid, for	KCC/A	
cooking ribs	KGC/A	
Chromed grid 1/1 GN	KG9G	
AISI 304 grid 1/1 GN	KG9GX	
AISI 304 vertical cooking grid for 8 chicken 1/1 GN	KGP	
AISI 304 Tray 1/1 GN	KT9G	
AISI 304 fat drip pan for chicken grids 1/1 GN	EKT11RGC	
Smooth plate with non-stick coa- ting 1/1 GN	KPGL11A	
Striped plate with non-stick coating 1/1 GN	KPGR11A	
AISI 304 Perforated tray 1/1 GN for cooking nuggets	EKTF 11	
Table	MKTS 11 C	
Table for overlapping ovens	MKT11DC	
Condensation hood	MKKC 610 C	
Kit for overlapping ovens	MKS 11 C	
Smoker	MKAF	
Fat concentrator	MKCG	
Multi-point core probe	MKSCMU	
Vacuum cooking core probe	MKSCSV	
Support for core probe	MKSSC	
Detergent and rinse aid	MKDET	
Spray kit with support and tube	EKKD	
Water softener	KAF	

Dimensional features

209 mm

172 mm

123 mm

138 mm

361 mm

429 mm

E

550

71 mm

Dimensions (WxDxH mm)	<mark>500</mark> x 930 x 970
Weight (kg)	94,6
Distance between rack rails (mm)	68

Electrical features

Electrical realtaries	
Power supply (kW)	15,4
Frequency (Hz)	50/60
Voltage (V)	AC 380/400 3N
N° motors	2 bidirectional
Boiler (kW)	/
Protection against water	IPX5

Functional features

i unetional reatares	
Power	Electricity
Capacity	N° 10 trays/grids 1/1 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 270 °C
Temperature control	Digital probe thermometer
Control panel	Touch screen
N° programs	500
Programmable cooking steps	10
Pre-heating temperature	180 °C
Pre-heating function	Programmable
Door	Right side opening Ventilated Inspectionable glass
Modularity	Yes
Feet	Adjustable